## Table of Contents

O	vervie	W	1
	1	Introduction	1
	2	Basic design	2
	3	Hardware systems	6
	4	Schedule	10
1	Physics requirements		1-1
	1.1	Energy asymmetry	1-1
	1.2	Luminosity	1-2
	1.3	Energy range	1-3
	1.4	Beam energy spread	1-4
	1.5	Beam background	1-4
2	Machine Parameters		2-1
	2.1	Luminosity, tune shift, and beam intensity	2-1
	2.2	Crossing angle	2-2
	2.3	Bunch length	2-5
	2.4	Bunch spacing	2-6
	2.5	Emittance	2-7
	2.6	Momentum spread and synchrotron tune	2-7
	2.7	Other issues	2-8
3	Beam-Beam Interactions		
	3.1	Introduction	3-1
	3.2	Simulation of beam collision	3-2
	3.3	Simulation with linear lattice functions	3-3
	3.4	Simulation with the lattice which includes nonlinearity	
		and errors	3-10
	3.5	Quasi strong-strong simulation	3-13
	3.6	Bunch tails excited by beam-beam interactions	3-15
	3.7	Tail, luminosity and longitudinal tilt	3-17
	3.8	Summary	3-19
	3.9	Comments on parasitic crossing effects	3-21
4	RF P	Parameters	4-1
	4.1	Introduction	4-1
	4.2	Requirements	4-2
	4.3	Cavity-related instabilities	4-3
		RF parameters	4-7

4.5	Summary	4-13
Impe	dance and Collective Effects	5-1
5.1	Impedance	5-1
5.2	Single-bunch collective effects	5-11
5.3	Coupled-bunch instabilities	5-12
5.4	Beam blow-up due to transient ion trapping in the electron ring	5-17
5.5	Instabilities due to beam-photoelectron interactions	5-23
Lattice Design		6-1
6.1	Dynamic aperture	6-1
6.2	Development of beam optics design	6-3
6.3	Optics design of the interaction region	6-13
6.4	Optics design of other straight sections	6-16
6.5	Requirements on the magnet quality	6-17
6.6	Effects of machine errors and tuning procedures	6-18
6.7	Conclusions	6-22
Interaction Region		7-1
7.1		7-1
7.2	Detector boundary conditions	7-4
7.3	Beam line aperture considerations	7-9
7.4	Superconducting magnets for IR	7-10
7.5	Special quadrupole magnets for IR	7-19
7.6	Installation and magnet support for IR	7-26
7.7	Beam background	7-28
RF System		8-1
8.1	Normal conducting cavity	8-1
8.2	Superconducting cavity	8-32
8.3	Low-level RF issues	8-43
8.4	Crab cavity	8-52
Magnet System		9-1
9.1	•	9-1
9.2	Magnet power supplies and cabling	9-15
9.3	Installation and alignment	9-18
Vacuum System		10-1
	-	10-1
	•	10-11
	Imper 5.1 5.2 5.3 5.4 5.5   Lattice 6.1 6.2 6.3 6.4 6.5 6.6 6.7   Inter 7.1 7.2 7.3 7.4 7.5 7.6 7.7   RF S 8.1 8.2 8.3 8.4   Magr 9.1 9.2 9.3   Vacu 10.1	Impedance and Collective Effects 5.1 Impedance 5.2 Single-bunch collective effects 5.3 Coupled-bunch instabilities 5.4 Beam blow-up due to transient ion trapping in the electron ring 5.5 Instabilities due to beam-photoelectron interactions  Lattice Design 6.1 Dynamic aperture 6.2 Development of beam optics design 6.3 Optics design of the interaction region 6.4 Optics design of other straight sections 6.5 Requirements on the magnet quality 6.6 Effects of machine errors and tuning procedures 6.7 Conclusions  Interaction Region 7.1 Beam-line layout 7.2 Detector boundary conditions 7.3 Beam line aperture considerations 7.4 Superconducting magnets for IR 7.5 Special quadrupole magnets for IR 7.6 Installation and magnet support for IR 7.7 Beam background  RF System 8.1 Normal conducting cavity 8.2 Superconducting cavity 8.3 Low-level RF issues 8.4 Crab cavity  Magnet System  9.1 Magnets in the arc and straight sections 9.2 Magnet power supplies and cabling

11	<b>Beam Instrumentation</b>	11-1
	11.1 Beam position monitor	11-1
	11.2 Optical monitor	11-9
	11.3 Laser wire monitor	11-19
	11.4 Bunch feedback system	11-23
12	Injection	12-1
	12.1 Linac	12-1
	12.2 Average Luminosity	12-24
	12.3 Beam transport	12-27
13	<b>Accelerator Control System</b>	13-1
	13.1 System requirements	13-1
	13.2 System architecture	13-5